

Portal Light 2 IR



Technical Specifications

Portal Light 2 IR

Physical

Height	2 in (50.8mm)
Width	0.74 in (18.82mm)
Depth	1.22 in (30.95 mm)
PCB dimensions	0.4 x 0.4 in (12 x 12 mm)
Weight	0.9 oz (26 grams) with standard cabling
Casing	IP 65; UL 94 VO
FI socket compatibility	Signify Luminaire-based brackets SA0200/05 and SA0200/15 for 60x22mm FI Luminaire slot Signify Luminaire-based brackets SA0100/05 for 44x17mm FI Luminaire slot Signify Ceiling-clips SA0600 and SA0500
Product identifier	MAC address, Unique ID
Visual status indicator	Illuminate during power-on
Product identification	MAC address (printed) Unique ID
IP protection	IP 65

Environmental

Operating temperature	14°F to 149°F (10°C to 65°C)
Storage temperature	-4°F to 185°F (-20°C to 85°C)
Operating humidity	10%-95% RH (non-condensing)
Storage humidity	5%-95% RH (non-condensing)

Electrical Power

Input voltage range	4.75V to 28V DC
Minimum continuous current-supply	5V: 250mA 12V: 54mA 24V: 50mA
Protection	Reverse Polarity
Power connection	Power Configuration: Hardwired Wire Exposure: Single external exposed wire; two internal lines Wire Color Coding: Red for positive, Black for negative Wire Type: AWG 20 (0.75mm ²) Wire Length: > 3.9 in. (10 cm) Wire Voltage Rating: up to 300V connection

Wi-Fi Radio

Wireless networking	IEEE 802.11 a/b/g/n
Frequency range	2.4GHz and 5GHz
Security	WEP, WPA™/ WPA2™ PSK, WPA2 Enterprise (EAP-TLS, EAP-TTLS, PEAPv0), WPA3™ Personal
Network communication	Hypertext Transfer Protocol Secure (HTTPS)/TLS 1.2
IP addressing	Dynamic Host Configuration Protocol (DHCP)
Data packet size	Typically less than 6 kilobytes (kB) per second

Technical Specifications

Portal Light 2 IR

Bluetooth Low Energy (LE) Radio	Wireless standard Range Output power Frequency range Work mode	Bluetooth LE 5.0 and 5.3 compatible Up to 98 feet (30 meters) 8 dBm 2.402GHz - 2.480GHz Central and Peripheral
IR (Infrared) Transmitter	Emitters Coverage area Minimum install height Maximum install height	4x 940 nm IR LED blasters 172 sq ft (16 sq m); installed height 9.8 ft (3 m) 7.8 ft. (2.4 m) 16.4 ft (5 m)
Features	Real Time Navigation Built-in IR transmitter sends room ID for easy, turn-by-turn wayfinding Cable Free Plugs into your existing smart light controller socket IT Friendly Works with your existing Wi-Fi network, Cisco, Wi-Fi 6, Kontakt.io, and other BLE gateways BLE Connected, Cloud Managed Easily push firmware over the air and monitor device health	
Certification	CE, UKCA, FCC, IC (ISED), WEEE, Reach & RoHS	



Get in Touch

Kontakt.io

Stoczniewców 3, 30-709
Kraków, Poland

T +48 123 793 445

E hello@kontakt.io

Kontakt.io

19 W 34 Street, Suite 1018,
New York, NY 10001

T +1 415-295-4558

E hello@kontakt.io