

Dispenser Beacon



Technical Specifications

Dispenser Beacon

Physical	Height Width Depth Weight Product identifier Mounting	3.1 in (80 mm) 2.7 in (70 mm) 1.9 in (50 mm) 3.4 oz (98 grams) QR code, MAC address, Unique ID Dispenser module insert Compatible with GOJO ES8 Dispenser
Environmental	Operating temperature Storage temperature Operating humidity Storage humidity	-13°F to 185°F (-25°C to 85°C) -4°F to 185°F (-20°C to 85°C) 10%-95% RH (non-condensing) 5%-95% RH (non-condensing)
Battery Power	Battery life Battery type Replaceable Power activation	Up to 2 to 3 years; 200k events AAA 2S2P 3.0V alkaline; 5000mAh Yes; supplied Kontakt.io battery pack Battery separator
Bluetooth Low Energy (LE) Radio	Wireless standard Range Output power (sensitivity) Frequency range	Bluetooth LE 5.0 and 5.3 compatible Up to 164 feet (50 meters) -96dBm 2.4GHz
Sensors	Temperature sensor	Range: -40°F to 185°F (-40°C to 85°C) Typical Accuracy: +/- 1.8°F (+/- 1°C)
Certifications	CE, FCC	



Get in Touch

Kontakt.io

Stoczniewców 3, 30-709
Kraków, Poland

T +48 123 793 445

E hello@kontakt.io

Kontakt.io

133 West 19th Street 7th Floor
New York, NY 10011

T +1 415-295-4558

E hello@kontakt.io